

TB Davies UNO Aluminium Industrial Tower



[Representative image of product]

Specifications

Brand: TB Davies
Warranty: 5-year
Max Load: 150kg
Standard: EN1004:2004
Material: Aluminium
Commodity Code: 76169990
Country of Origin: UK

Common Dimensions

- Platform Length: 1300mm - Platform Width: 700mm

- Distance Between Rungs: 250mm

- Recommended Usage: Intensive

Packaging Material

- Polywrap

Availability & Delivery

- Non-stock item. Delivery up to 7 days.

Product Description

Heavy-duty single width scaffold tower that certified to BS EN1004 standards. Easy to erect and dismantle by one person with the base unit forming a trolley for fast storage and transportation.

Features

- Compact tower unit that fits through standard doorways (800mm)
- 1 x size frame for an easier build
- Aluminium tower & toe board with heavy-duty plywood platform
- Multiple platform heights up to 4.1m
- 250mm rung pitch
- Designed for one person to install without extra assistance

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

Date Created: July 16th, 2024



TB Davies UNO Aluminium Industrial Tower

Product Dimensions

SKU	Platform Height ² (mm)	Approx. Working Height ¹ (mm)	Overall Height (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3020-200	4100	5850	5300	3262 x 2468	130.0†

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

² Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.