

INSUL8-S Fibreglass Professional Swingback Step



[Representative image of product]

Product Description

Our Fibreglass StepLadder range incorporates a multi-functional tool tray with non-conductive stiles, making them ideal for working around electricity. The combination of super-strong C-section fibreglass stiles and reinforced aluminium treads gives you a durable yet lightweight and easy to handle step that is perfect for the busy tradesperson.

Features

- Non-conductive fibreglass stiles to 30,000 volts (EN61478), ideal for working around electricity
- Integrated multi-function tool tray
- Comfortable 80mm treads
- Hinged metal locking stays, provide optimal stability
- Box section back legs with heavy-duty bracing
- Large feet angled to maximise ground contact and reduce slip

Specifications

- Brand: TB Davies
- Warranty: 3-year
- Max Load: 150kg
- Standard: EN131 PROFESSIONAL
- Material: GRP Fibreglass/Aluminium
- Commodity Code: 39269097
- Country of Origin: CN
- Recommended Usage: Regular

Common Dimensions

- Tread Depth: 80mm
- Distance Between Treads: 280mm
- Storage Depth: 153mm

Packaging Material

- Polythene Wrap & Cardboard Header Card

Availability & Delivery

- Stock item. Delivery next day.
- (See exceptions, if applicable, overleaf)



INSUL8-S Fibreglass Professional Swingback Step

Product Dimensions

SKU	Treads ²	Max. Step Height (mm)	Approx. Working Height ¹ (mm)	Closed Height (mm)	Open Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1235-004	4	257	2007	1143	1028	452	826	5.7
1235-005	5	518	2268	1423	1289	486	1006	7.0
1235-006	6	779	2529	1703	1550	520	1187	8.0
1235-008	8	1303	3053	2263	2074	589	1547	10.5
1235-010	10	1825	3575	2823	2596	657	1908	13.1

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate.
Ladders set at an angle of ~75° degrees.
² Tread count includes the top platform step/top cap tool tray tread.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
1235-004	1143	386	153	0.068	5.9
1235-005	1423	403	153	0.088	7.2
1235-006	1703	420	153	0.109	8.2
1235-008	2263	455	153	0.158	10.7
1235-010	2823	488	153	0.211	13.3