

INSUL8-P Fibreglass Professional Platform Step



[Representative image of product]

Product Description

Our Heavy-Duty Fibreglass step ladder range incorporates a multi-functional tool tray with non-conductive stiles, making them ideal for working around electricity. The combination of super-strong C-section fibreglass stiles and reinforced aluminium treads gives you a durable yet lightweight and easy to handle step that is perfect for the busy trades-person.

Features

- Non-conductive fibreglass stiles to 30,000 volts (EN61478), ideal for working around electricity
- Integrated multi-function tool tray
- Reinforced 320 x 248mm checker-plate platform (platform steps only)
- Comfortable 80mm treads
- Hinged metal locking stays, provide optimal stability
- Box section back legs with heavy-duty bracing
- Large feet angled to maximise ground contact and reduce slip

Specifications

- Brand: TB Davies
- Warranty: 3-year
- Max Load: 150kg
- Standard: EN131 PROFESSIONAL
- Material: GRP Fibreglass/Aluminium
- Commodity Code: 39269097
- Country of Origin: CN
- Recommended Usage: Regular

Common Dimensions

- Tread Depth: 80mm
- Distance Between Treads: 280mm
- Storage Depth: 153mm
- Top Platform Tread (LxW): 345 x 255mm
- Handrail Height: 607mm

Packaging Material

- Polythene Wrap & Cardboard Header Card

Availability & Delivery

- Stock item. Delivery next day.
(See exceptions, if applicable, overleaf)

INSUL8-P Fibreglass Professional Platform Step

Product Dimensions

| SKU | Treads ² | Platform Height (mm) | Approx. Working Height ¹ (mm) | Closed Height (mm) | Open Height (mm) | Width (mm) | Open Depth (mm) | Nett Weight (kg) |
|----------|---------------------|----------------------|--|--------------------|------------------|------------|-----------------|------------------|
| 1236-004 | 4 | 1041 | 2791 | 1808 | 1648 | 537 | 994 | 8.8 |
| 1236-005 | 5 | 1303 | 3053 | 2088 | 1910 | 572 | 1174 | 10.2 |
| 1236-006 | 6 | 1564 | 3314 | 2368 | 2171 | 606 | 1354 | 11.4 |
| 1236-008 | 8 | 2087 | 3837 | 2928 | 2694 | 674 | 1715 | 14.0 |

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

² Tread count includes the top platform step/top cap tool tray tread.

Shipping Dimensions

| SKU | Shipping Length (mm) | Shipping Width (mm) | Shipping Depth (mm) | Shipping Volume (m ³) | Gross Weight (kg) |
|----------|----------------------|---------------------|---------------------|-----------------------------------|-------------------|
| 1236-004 | 1808 | 430 | 153 | 0.119 | 9.0 |
| 1236-005 | 2088 | 445 | 153 | 0.142 | 10.4 |
| 1236-006 | 2368 | 460 | 153 | 0.167 | 11.6 |
| 1236-008 | 2928 | 497 | 153 | 0.223 | 14.2 |

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

TB Davies (Cardiff) Ltd, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 www.tbdavies.co.uk Registered in England No.534073, VAT Reg. No.GB134144207
 Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.